



# BUILT FOR TRAVEL

UCA & LONG TRAVEL SUSPENSION **SALES GUIDE** 



# STOCK LENGTH UPPER CONTROL ARMS

## 1996 - 2004 TACOMA 4WD / PRERUNNER - 6 LUG



### PART # 96500



Travel	Lift	Track Increase
1" additional	2-3"	0"



INSTALLATION INSTRUCTIONS



**ADDITIONAL PRODUCT INFO & IMAGES** 

#### Bolt On

#### **Optional Heim Pivot Upgrade**

- TC includes 3/4" chromoly heim joints for the pivots.
- Heim upper control arms are fully adjustable to allow maximum tuning of caster and camber.
- Designed for use on 6" or higher drop bracket lift kits.

#### Kit Includes UPPER A-ARMS W/ BUSHINGS PLATED END WASHERS 1" UNIBALLS W/ RETAINING CLIPS **GRADE 8 HARDWARE** GREASE FITTINGS **BILLET SLUG ADAPTER**

#### Features and Benefits

- UCA's are designed with added caster to aid in retaining factory alignment specs when aftermarket lift kits are installed. This reduces the darting or wandering in the vehicle's steering when 2.5"-3" lift kits are installed.
- Upper control arms combined with extended length coil over shocks will allow for up to 1" of additional wheel travel.
- Urethane bushings reduce bushing deflection compared to stock rubber bushings.
- CNC machined slug adapters press into the spindle and convert the factory ball joint to a 1" uniball for added component strength & maximum wheel travel.
- TOTAL CHAOS includes 1″I.D. uniballs that feature a heat treated stainless steel ball & heat treated stainless steel race for maximum corrosion resistance and component longevity. These uniball's also features a military grade PTFE

- woven fabric liner that helps prevent noise.
- Custom profile upper and lower hi-misalignment spacers maximize droop wheel travel and are machined from heat treated 17-4 stainless steel. The lower himisalignment spacer registers into the slug adapter for maximum strength.
- 4130 chromoly tubular upper control arms are 100% bolt on and hand crafted in the U.S.A.
- Control arm pivots include zerk fittings to grease the urethane bushings & inner sleeves without disassembly.
- 3 stage powder coat process includes a durable clear coat to provide a long lasting finish.
- Complete grade 8 hardware kit is included.
- \*Not compatible with lift kits from Tuff Country.

#### Recommended Tire & Wheel Combination

Tire	Wheel	Backspace
285/75/R16	16 x 8	4.5"
285/70/R17	17 x 8.5	4.75"

Recommended Primary Shock Setup 2.5" Diameter Extended Travel Coilover Shocks

Shock Manufacturer	Part #
Fox Shocks	880-06-409
King Shocks	KNG-25001-151-EXT

SUPPORT - (951) 737 9682



# **TOYOTA TACOMA STOCK LENGTH ACCESSORIES**

### **FRONT**

# ACCESSORIES SPECIFIC TO PART #96500



#### KING 2.5" EXTENDED TRAVEL COILOVERS W/ COMPRESSION KNOBS



- Adjustable ride height ranging from 2"-3" of lift.
- 1" extra droop wheel travel when combined with 96500 upper control arms.
- Compression adjuster knobs allow user to fine tune ride for optimum performance.
- All necessary mounting brackets and hardware are included along with detailed instructions.

Part # KNG-25001-151-EXT



LOWER CONTROL ARM CAM TAB GUSSETS

to the frame.

like factory tabs.

#### SPINDLE GUSSET



- Must have reinforcement for anyone who wants to run hard in the dirt!
- Strengthens spindle uprights and prevents the knuckle from damage during hard impacts under braking.
- 1/8" prebent laser cut mild steel brackets.
- Eliminates the factory sway bar.
- Welding and grinding are required to install.

Part # 59697







- Eliminates sloppy steering and unwanted rack movement caused by worn out rubber bushings.
- 100% bolt-on.
- Replaces all three factory rubber bushings.



Part # 59960

#### **COIL BUCKET TOWER GUSSETS**



 Reduces upper coil bucket flex and double shears factory upper control arm bolt.

■ Reinforces weak factory cam alignment tab plates

■ CNC laser cut 1/8" 4130 chromoly cam plates weld

1/4" thick lower cam alignment tabs will not bend

that bend during bottom outs or hard front

Welding and grinding are required to install.

- Compatible only with TC UCA's or L/T kits not intended for use with factory control arms.
- Welding and grinding are required to install.

Part # 59650





#### SECONDARY SHOCK HOOP KIT



Part # 96602

- Maximize vehicle dampening control when you install a dual 2.5" shock mount system.
- 4130 prebent chromoly shock hoops are designed to install secondary 2.5" smooth body or bypass shocks for maximum IFS dampening control.
- Kit includes weld-on lower shock mounts for factory lower control arms.
- Reinforces the factory coil bucket and helps reduce flex.
- Upper shock tabs are tacked in place to aid in secondary shock location set up.
- Includes Grade 8 hardware.
- Welding and grinding are required to install.

#### KING 2.5" EXTERNAL BYPASS SECONDARY SHOCKS



- Designed for use with TC secondary shock hoops (PN: 96602).
- Externally adjustable compression and rebound tubes
- 2.5" diameter with remote reservoirs.

Part #

KNG-PR2506-BP2P



ACCESSORIES SPECIFIC TO PART #96500

# **TOYOTA TACOMA STOCK LENGTH ACCESSORIES**

#### REAR



#### **REAR 2.0" SHOCK MOUNT KIT**



Part # 49625

- Maximizes articulation while navigating over obstacles and provides +3" of additional droop wheel travel and better ride quality.
- Outboard shock mounting location provides additional dampening control.
- Utilizes a 2.0" emulsion, reservoir or bypass shock from FOX or KING.
- Compatible with the TOTAL CHAOS rear 2.0" bump stop kit. PT# 49623F/49623K
- 3/16" mild steel upper and lower laser cut shock mounts are included. Welding is required for installation.
- 1.25" wheel spacers must be installed.
- Grade 8 hardware included.



#### KING 2.0" EXTERNAL BYPASS SHOCKS



- Designed for use with TC secondary shock hoops (PN: 96602).
- Requires a lower control arm with dual shock capability.
- Externally adjustable compression and rebound tubes.
- 2.5" diameter with remote reservoirs.

Part # KNG-PR2010-BP2P



#### 3-LEAF ADD-A-PACK (PAIR) 1.5" LIFT TACOMA



- Designed to be added to your truck's existing leaf pack.
- Replaces overload leaf giving the ride a more progressive feel.
- Provides 1.5" of lift to the truck.
- Sold as a pair.

Part # DVR-F85



#### KING BUMP STOP 2.0" x 2.0" TRAVEL (FITS PN: 48623K)



- Double sealed Schrader cover that mounts to the body, not the valve itself creates a positive seal and keeps dirt and moisture out.
- Unique mounting boss design with indexing pin securely locates the bump stop without pinching the outside of the tube.
- Aluminum components are machined from aircraft quality billet.
- Large diameter shafts have a minimum tensile strength of 75,000 PSI.

Part # KNG-BS2020

- Long wearing nylon contact pad ensures quiet operation and mounts with a simple yet effective single bolt design.
- Sold individually.



#### WELD ON 2.0" REAR BUMP STOP KIT [KING]



Part # 49623K

- Weld on bump stop bracket indexes above and below the frame for maximum strength.
- Utilizes 2" travel KING 2.0" diameter bump stops.
- Increases handling and performance on and off road when weight has been added to the bed of the truck.
- Cushions harsh bottom outs.
- Includes lower strike pad that bolts to the factory U bolt location.
- Grade 8 hardware is included.
- 1.25" wheel spacers must be installed.



#### WELD ON 2.0" REAR BUMP STOP KIT [FOX]



Part # 49623F

- Weld on bump stop bracket indexes above and below the frame for maximum strength.
- Utilizes 2.5" travel FOX 2.0" diameter bump stops.
- Increases handling and performance on and off road when weight has been added to the bed of the truck.
- Cushions harsh bottom outs.
- Includes lower strike pad that bolts to the factory U bolt location.
- Grade 8 hardware is included.
- 1.25" wheel spacers must be installed.

SUPPORT - (951) 737 9682





# TOYOTA TACOMA STOCK LENGTH ACCESSORIES





#### 1" STAINLESS STEEL FK UNIBALL AND SNAP RING REPLACEMENT KIT



- 1″ I.D. uniballs feature a heat treated stainless steel ball & heat treated stainless steel race for maximum corrosion resistance and component longevity.
- Performance parts will require periodic maintenance based on your driving habits & local
- Uniballs include a military grade PTFE woven fabric liner that helps prevent noise.
- Snap rings included.
- Sold as a pair.

Part # FK-REP KIT



#### 1" UNIBALL REMOVAL / INSTALL TOOL



- Aids in the removal and reinstallation of a 1" uniball from any uniball cup during vehicle prep.
- Designed to be used with any hydraulic press, shop press or hammer.
- Prevents damage to new uniball during reassembly.

Part # 96006





#### **URETHANE BUSHING KIT: UPPER CONTROL ARMS**



Part # 69000

- Complete TC upper control arm urethane replacement bushing kit.
- Performance parts will require periodic maintenance based on your driving habits & local
- Inspect bushings and other equipment regularly.
- Contact our facility direct to order these items.




# 3.5" BOXED LONG TRAVEL SYSTEM

# 1996 - 2004 TOYOTA TACOMA 4WD / PRERUNNER - 6 LUG



#### PART #96000BK [KING/FOX]



Travel	Lift	Track Increase
13"	3-4"	7"



**INSTALLATION INSTRUCTIONS** 



**ADDITIONAL PRODUCT INFO & IMAGES** 

**Bolt On** 

Kit Includes
UPPER A-ARMS W/ BUSHINGS & ZERK FITTINGS
LOWER A-ARMS W/ BUSHINGS
TIE-ROD EXTENSIONS
PLATED A-ARM END WASHERS
D.O.T. BRAIDED BRAKE LINES
1" UNIBALLS W/ RETAINING CLIPS
BOLT-ON UPPER SHOCK MOUNTS
LIMIT STRAPS W/ ADJUSTERS & MOUNTS
GRADE 8 HARDWARE
HI-MISALIGNMENT SPACERS

#### **Features and Benefits**

- 3.5" extended upper and lower control arms bolt to factory mounting locations. Fiberglass fenders are required. 13" Travel.
- Upper ball joints are upgraded to 1" stainless steel uniballs for max travel and component strength.
- Boxed lower control arms are designed with internal gussets and are pre tabbed for dual 2.5" shock capability.
- Several spring rate options allow the ability to customize your ride for your specific application.

- Primary coil over shocks bolt into the factory coil bucket location to maximize tunability, overall articulation & performance.
- Optional remanufactured Tundra axles and CV joints that are custom modified by TC to retain 4WD. (not included)
- Race proven IFS equipment in China, Baja and South America!
- Heim pivot upper control arms can be custom ordered for this kit (see next page).

# Recommended Tire & Wheel Combination

Tire	Wheel	Backspace
285/75/R16	16 x 8	4.5"
285/70/R17	17 x 8.5	4.75"

# Recommended Primary Shock Setup 2.5" Diameter Extended Travel Coilover Shocks

Shock Manufacturer	Part #
Fox Shocks	883-02-056
King Shocks	KNG-TC5151-03

# Recommended Secondary Shock Setup 2.5" External Bypass Shocks

Shock Manufacturer	Part #
Fox Shocks	982-02-954
King Shocks	TC-1151-34

Note: TC Hoop Part # 96601 is required

#### Required Additional Parts for Installation

Part	Part #
Coilover Shocks	See Above Table
TC Extended Axles (4WD MODELS )	96300 (auto hubs only)

#### **Application Notes**

- Suspension travel varies on every vehicle. Welding is required to mount the limit strap mounts and bump stop spacer.
- This kit was not intended to use air bumps.

SUPPORT - (951) 737 9682



# 3.5" BOXED LONG TRAVEL SYSTEM W/ HEIMS 1996 - 2004 TOYOTA TACOMA 4WD / PRERUNNER - 6 LUG

## A

#### PART #96000BK-H [KING/FOX]



Travel	Lift	Track Increase
13"	3-4"	7"



INSTALLATION INSTRUCTIONS



**ADDITIONAL PRODUCT INFO & IMAGES** 

**Bolt On** 

Kit Includes
UPPER A-ARMS W/ HEIMS
LOWER A-ARMS W/ BUSHINGS
TIE-ROD EXTENSIONS
D.O.T. BRAIDED BRAKE LINES
1" UNIBALLS W/ RETAINING CLIPS
BOLT-ON UPPER SHOCK MOUNTS
LIMIT STRAPS W/ ADJUSTERS & MOUNTS
GRADE 8 HARDWARE
HI-MISALIGNMENT SPACERS

#### **Features and Benefits**

- 3.5" extended upper and lower control arms bolt to factory mounting locations. Fiberglass fenders are required. 13"Travel.
- Upper ball joints are upgraded to 1" stainless steel uniballs for max travel and component strength.
- 4130 chromoly tubing heim upper control arms are fully adjustable to allow maximum tuning of caster and camber.
- Primary coil over shocks bolt into the factory coil bucket location.

- Boxed lower control arms include dual 2.5" shock tabs.
- Several spring rate options allow the ability to customize your ride for your specific application.
- Maximize tune ability, overall articulation & performance.
- Optional remanufactured Tundra axles and CV joints that are custom modified by TC to retain 4WD (not included).

# Recommended Tire & Wheel Combination

Tire	Wheel	Backspace
285/75/R16	16 x 8	4.5"
285/70/R17	17 x 8.5	4.75"

# Recommended Primary Shock Setup 2.5" Diameter Extended Travel Coilover Shocks

Shock Manufacturer	Part #
Fox Shocks	883-02-056
King Shocks	KNG-TC5151-03

# Recommended Secondary Shock Setup 2.5" External Bypass Shocks

Shock Manufacturer	Part #	
Fox Shocks	982-02-954	
King Shocks	TC-1151-34	

Note: TC Hoop Part # 96601 is required

#### Required Additional Parts for Installation

Part	Part #
Coilover Shocks	See Above Table
TC Extended Axles (4WD MODELS )	96300 (auto hubs only)

#### **Application Notes**

- Suspension travel varies on every vehicle. Welding is required to mount the limit strap mounts and bump stop spacer.
- This kit was not intended to use air bumps.

SUPPORT - (951) 737 9682

### **FRONT**

ACCESSORIES SPECIFIC TO PART # 96000BK & 96000BK-H



#### KING LONG TRAVEL COILOVERS



- Long travel specific shocks add 3-4" of lift when paired with a TC long travel kit.
- 2.5" diameter shocks with remote reservoirs for optimum cooling.



#### KING LONG TRAVEL SECONDARY SHOCKS



- Serious levels of performance are achieved when a secondary shock is used with a TC long travel kit.
- Externally adjustable for both compression and rebound.
- Designed for use with TC secondary shock hoops (PN: 99601).



Part # KNG-TC5151-03



Part # KNG-TC1151-34



#### **WELD - ON SPINDLE GUSSETS**



- Must have reinforcement for anyone who wants to run hard in the dirt!
- Strengthens spindle uprights and prevents the knuckle from damage during hard impacts under
- 1/8" prebent laser cut mild steel brackets.
- Eliminates the factory sway bar.
- Welding and grinding are required to install.



#### LONG TRAVEL HEIM JOINT STEERING UPGRADE



- Maximize wheel travel and component strength while eliminating sloppy steering.
- 4130 zinc plated extended chromoly tie-rods.
- 7/8" 4130 chromoly heim joints replace factory outer tie rod ends.
- Laser cut weld-on double shear steering arm gussets are included.
- Grade 8 hardware and tapered steering arm adapters are supplied.
- Designed to fit TC long travel systems ONLY.

59697



Part # 96099



#### **WELD - ON UPPER COIL BUCKET TOWER GUSSETS**



- Reduces upper coil bucket flex and double shears factory upper control arm bolt.
- Compatible only with TC UCA's or L/T kits, not intended for use with factory control arms.
- Welding and grinding are required to install.



Part # 59650



#### LOWER CONTROL ARM CAM TAB GUSSETS



Part # 59960

- Reinforces weak factory cam alignment tab plates that bend during bottom outs or hard front
- CNC laser cut 1/8" 4130 chromoly replacement cam plates weld-to the frame.
- 1/4" thick lower cam alignment tabs will not bend like factory tabs.
- Welding and grinding are required for installation.

SUPPORT - (951) 737 9682



ACCESSORIES SPECIFIC TO PART # 96000BK & 96000BK-H

## **FRONT**



#### **URETHANE STEERING RACK BUSHING KIT**



- Eliminates sloppy steering and unwanted rack movement caused by worn out rubber bushings.
- 100% bolt on.
- Replaces all three factory rubber bushings.





#### **DUAL SHOCK HOOPS - LONG TRAVEL ARMS**



Part # 96601

- Maximize vehicle dampening control when you install a dual 2.5" shock mount system.
- 4130 prebent chromoly shock hoops are designed to install secondary 2.5" smooth body or bypass shocks for maximum IFS dampening control.
- Reinforces the factory coil bucket and helps reduce
- Upper shock tabs are tacked in place to aid in secondary shock location set up.
- Includes grade 8 hardware.
- Welding and grinding are required to install.



#### 24" Brake Lines



- Replacement front brake lines for use with 3.5" long travel kit only.
- Braided stainless steel construction.
- Kit includes mounting clips and copper washers.
- Sold as a pair.



96330



4WD



#### LT 4WD MODIFIED AXLES +3.5" EXTENDED



- Designed for use with TC +3.5" long travel systems.
- Includes remanufactured Tundra axles and CV joints that are custom modified by TC.
- High angle inner CV boots and clamps are installed.
- Fits auto hub trucks only.



#### 1" DIFF. DROP SPACER KIT



- Tired of tearing inner CV boots when aftermarket lift kits have been installed?
- Reduces inner CV angle by 2-3 degrees.
- Reduces friction wear and tear on stock length axle inner CV boots with auto locking hubs.

Part # 96300



Part # 96200

# LONG TRAVEL SUSPENSION

# TOYOTA TACOMA ACCESSORIES FOR 3.5" KITS

ACCESSORIES SPECIFIC TO PART # 96000BK & 96000BK-H

REAR



#### **KING REAR BYPASS SHOCKS**



- 2.5" shock bodies with piggyback reservoir.
- 16" shock stroke.
- Compression and dampening adjustable for maximum performance.
- Requires rear bed cage to install.



#### **WELD-ON REAR AXLE SHOCK MOUNTS**



- Laser cut 1/4" thick plates are pre welded with gussets that are designed to protect lower shock rod ends.
- Places lower shock eyelet 7" off of housing.
- Intended for 3" axle housings, can be ground to fit larger applications.

Developed to relocate front spring hangers for leaf

Laser cut brackets weld to frame and include grade

Designed to use 2.5" aftermarket leaf springs.

Grinding and welding are necessary to install.

- Grade 8 hardware included.
- Welding is required to install.

Part # 40080


Part # KNG-PR2516-BP3P



#### **HEAVY DUTY U-BOLT RELOCATION PLATES**



- Designed to protect u-bolt nuts.
- Recesses leaf spring pin into plate to prevent shifting.
- Designed for 62" spring under setup.
- Intended to be installed with 2.5" wide after market leaf springs mounted under the rear axle.
- 100% bolt on.





Part # 40020-HD



#### **SHACKLE PIVOT GUSSETS (SET OF 4)**



- Designed to reinforce and strengthen the mounting location on top or below the frame rail where TC 9" or 12" shackles have been mounted.
- Laser cut 10 gauge gussets are pre bent and notched ready to weld.
- Grinding and welding are necessary for installation.

Part # 40450



Part # 40060

#### 12" SHACKLE W/ BUSHINGS (PAIR)

62" LEAF SPRING WELD-ON FRONT HANGERS

8 hardware.

spring conversions.



- 4130 chromoly tubing 12" long shackles.
- Designed to be installed with 2.5" wide leaf spring applications.
- Grade 8 hardware and urethane bushings are included.
- Custom fabrication is required for installation.

Part # 41200



#### **AXLE PERCH**



- Used to relocate leaf springs from top of axle housing to bottom when mounting Deaver leaf springs (Part #: F67).
- Welding required for installation.



#### DEAVER 61.5" (12.5" ARC) LEAF SPRINGS



- Commonly used for a spring under conversion which increases wheel travel without excessively lifting the vehicle.
- Higher leaf count springs allow the use of thinner leaf material resulting in a more flexible and progressive leaf stack.
- Capable of 16" of travel.

Part # DVR-F67







ACCESSORIES SPECIFIC TO PART # 96000BK & 96000BK-H

**REAR** 



#### **26" REAR BRAKE LINES**



- Longer main brake line to rear end T-junction needed when running long travel.
- Constructed from braided stainless steel.



#### KING BUMP STOP 2.0" x 2.0" TRAVEL (REQUIRES PN: 48623K)

keeps dirt and moisture out.



 Unique mounting boss design with indexing pin securely locates the bump stop without pinching the outside of the tube.

Double sealed Schrader cover that mounts to the

body, not the valve itself creates a positive seal and

- Aluminum components are machined from aircraft quality billet.
- Large diameter shafts have a minimum tensile strength of 75,000 PSI.
- Long wearing nylon contact pad ensures quiet operation and mounts with a simple yet effective single bolt design.
- Sold individually for install with PN: 48623K.

Part # 43326



Part # KNG-BS2020

# P

#### WELD ON 2.0" REAR BUMP STOP KIT [FOX]



49623F

- Weld on bump stop bracket indexes above and below the frame for maximum strength.
- Utilizes 2.5" travel FOX 2.0" diameter bump stops.
- Increases handling and performance on and off road when weight has been added to the bed of the truck.
- Cushions harsh bottom outs.
- Includes lower strike pad that bolts to the factory U bolt location.
- Grade 8 hardware is included.
- 1.25" wheel spacers must be installed.



#### WELD ON 2.0" REAR BUMP STOP KIT [KING]



49623K

- Weld on bump stop bracket indexes above and below the frame for maximum strength.
- Utilizes 2" travel KING 2.0" diameter bump stops.
- Increases handling and performance on and off road when weight has been added to the bed of the truck.
- Cushions harsh bottom outs.
- Includes lower strike pad that bolts to the factory U bolt location.
- Grade 8 hardware is included.
- 1.25" wheel spacers must be installed.

**PREP** 



#### 1" STAINLESS STEEL UNIBALL REPLACEMENT KIT



- 1"I.D. uniballs feature a heat treated stainless steel ball & heat treated stainless steel race for maximum corrosion resistance and component longevity. These uniball's also features a military grade PTFE woven fabric liner that helps prevent noise.
- Snap rings included.



#### UNIBALL REMOVAL & RE-INSTALLATION TOOL





- Aids in the removal and reinstallation of a 1" uniball from any uniball cup during vehicle prep.
- Designed to be used with any hydraulic press, shop press or a hammer.
- Prevents damage to new uniball during reassembly.

Part #

96006



FK-REP KIT



ACCESSORIES SPECIFIC TO PART # 96000BK & 96000BK-H

**PREP** 



#### LONG TRAVEL URETHANE BUSHING KIT



- Complete TC long travel suspension system replacement urethane bushing kit.
- Performance parts will require periodic maintenance based on your driving habits & local
- Inspect bushings and other equipment regularly.



#### LONG TRAVEL URETHANE BUSHING KIT W/ HEIM UCAS



- Replacement bushings for TC long travel kits that have heim upper control arms.
- Performance parts will require periodic maintenance based on your driving habits & local
- Inspect bushings and other equipment regularly.

Part # 69650



69600



#### **BALL JOINT REMOVAL- SLUG ADAPTER INSTALL TOOLS**



- Aids in the removal of the factory ball joint from the
- Also designed to assist in the TC slug adapter installation.
- Requires a large C clamp tool or press tool.

96005



#### **ADDITIONAL REPLACEMENT PARTS**

- TC stocks all replacement parts necessary to maintain your performance equipment.
- Tie-Rod Extensions
- Plated A-Arm End Washers
- D.O.T. Braided Brake Lines
- Limit Straps w/ Adjusters & Mounts
- Grade 8 Hardware
- Hi-Misalignment Spacers
- Please have your customers contact TC directly for any individual replacement parts.



SUPPORT - (951) 737 9682